



GENERATORS

www.vipergen.co.za

Kwa-Zulu Natal
 134 Shepstone Road
 New Germany, 3610
 Tel: 031-705 4104
 Fax: 031-705 4542

Gauteng
 75 Watt Street
 Meadowdale, 1614
 Tel: 011-974 0400
 Fax: 011-974 0554

Model: 60kVA 3 PHASE

POWER DATA

Voltage	Prime Power		Standby Power		Standby AC	No. of Phase
	kva	kw	kva	kw	Amps Per Phase	
220/380V	60	48	65	52	98.8	3
230/400V	60	48	65	52	93.9	3
240/415V	60	48	65	52	90.5	3
254/440V	60	48	65	52	85.4	3

ENGINE DATA

Manufacturer	R Series (British Ricardo)	Compression Ratio	17.5:1
Origin	British	Oil Capacity (L)	11
Model	R4105ZDI	Electrical System	12V
Governor Type	Mechanical	Coolant Capacity (L)	20
Speed	1500rpm	Fuel Consump. (100%load)(L/HR)	15.3
Prime Power (kw)	60	Fuel Tank Capacity (L)	236
Standby Power (kw)	63	Cooling	Water Cooled
Cylinder No. & Config.	4 in Line	Aspiration	Turbo

ALTERNATOR DATA

Manufacturer	Marathon or Stamford	Voltage (V)	220/380
Origin	U.S	Voltage Accuracy	± 1%
Model	MP48-4/WHI-50-4	Frequency	50Hz
Capacity (kva)	62.5	Insulation Class	H
Power Factor	0.8	Protection Rate	IP21 / IP23
Efficiency	88%	Excitation System	Brushless, AVR
Bearing Number	Single	Connection Type	Star
Leads Number	12		

OVERALL DIMENSIONS & WEIGHT

Genset Size (mm) (L x W x H)	2500 x 1050 x 1560
Net Weight (kg)	1400



KEY FEATURES

1. Durable British Ricardo Series Engine
2. Single Bearing Marathon Type Alternator
3. ATS & AMF
4. Four Protection Device Equipped
5. Anti-Vibration Mountings
6. Main Line Circuit Breaker
7. Factory Test Certificate
- 8.Noise Level @7m (db): 80

STANDARD CONTROL SYSTEM

The Standard control system is based on the advanced smartgen HGM7220 Electronic Digital Controller.

This Provides for the manual and automatic remot start of generator with a LCD digital display of:

1. Coolant Temperature
2. Oil Pressure
3. Volts, Amps, Power Factor & Frequency
4. Engine Operation Hours
5. Over Current Protection
6. Under, Over Volt Protection
7. Over Temperature Protection
8. Over Speed, Low Oil Pressure Protection

