



GENERATORS

www.vipergen.co.za

Kwa-Zulu Natal
 134 Shepstone Road
 New Germany, 3610
 Tel: 031-705 4104
 Fax: 031-705 4542
Gauteng
 75 Watt Street
 Meadowdale, 1614
 Tel: 011-974 0400
 Fax: 011-974 0554

Model: 375kVA 3 PHASE SYNCHRONISE

POWER DATA

Voltage	Prime Power		Standby Power		Standby AC	No. of Phase
	kva	kw	kva	kw	Amps Per Phase	
220/380V	375.0	300.0	413.0	330.0	569.8	3
230/400V	375.0	300.0	413.0	330.0	541.3	3
240/415V	375.0	300.0	413.0	330.0	521.7	3

ENGINE DATA

Manufacturer	SDEC	Compression Ratio	17:01
Model	SC13E500D2	Oil Capacity (L)	36.0
Governor Type	Electronic	Electrical System	24V
Speed	1500rpm	Coolant Capacity (L)	75.0
Prime Power (kw)	339.0	Fuel Consump. (100%load)(L/HR)	74.6
Standby Power (kw)	373.0	Fuel Tank Capacity (L)	850
Cylinder No. & Config.	6 in Line	Cooling	Water Cooled
Bore x Stroke	130 x 161	Aspiration	Turbo
		Displacement	12.8

ALTERNATOR DATA

Manufacturer	LONGEN	Voltage (V)	220/380
Model	WH14F	Voltage Accuracy	± 1%
Capacity (kva)	375.0kVA	Frequency	50Hz
Power Factor	0.8	Insulation Class	H
Efficiency	94.4%	Protection Rate	IP23
Bearing Number	Single	Excitation System	Brushless, AVR
Leads Number	12	Connection Type	Star

OVERALL DIMENSIONS & WEIGHT

Genset Size (mm) (L x W x H) Net 3900 x 1600 x 2350
 Weight (kg) 4380



KEY FEATURES

1. Durable SDEC "E" Series Engine
2. Single Bearing Stamford Type Alternator
3. ATS & AMF
4. Four Protection Device Equipped
5. Anti-Vibration Mountings
6. Main Line ACB Circuit Breaker
7. Factory Test Certificate
8. Noise Level @7m (db): 90

STANDARD CONTROL SYSTEM

The Standard control system is based on the advanced smartgen HGM9510N Synchronizing Electronic Digital Controller. This Provides for the manual and automatic remot start of generator with a LCD digital display of:

1. Coolant Temperature
2. Oil Pressure
3. Volts, Amps, Power Factor & Frequency
4. Engine Operation Hours
5. Over Current Protection
6. Under, Over Volt Protection
7. Over Temperature Protection
8. Over Speed, Low Oil Pressure Protection

